

| | |
|---|---|
| Misfire detection adaptation, range 0 | 6 |
| Reset counter: plaus. test FSE | 0.0 |
| Retardation cylinder 1 | 0.00 °KW |
| Retardation cylinder 6 | 0.00 °KW |
| Retardation cylinder 2 | 0.00 °KW |
| Retardation cylinder 4 | 0.00 °KW |
| Retardation cylinder 3 | 0.00 °KW |
| Retardation cylinder 5 | 0.00 °KW |
| Ignition safety retardation | 0 |
| Ignition map RON dependent | 0.0 |
| Number of ignitions at speed > maximum speed, range 1 | 1419 |
| Number of ignitions at speed > maximum speed, range 2 | 364 |
| Number of ignitions at speed > maximum speed, range 3 | 150 |
| Number of ignitions at speed > maximum speed, range 4 | 73 |
| Number of ignitions at speed > maximum speed, range 5 | 0 |
| Number of ignitions at speed > maximum speed, range 6 | 0 |
| Operating hours counter reading at overspeed, range 1 | 1690.100 h |
| Operating hours counter reading at overspeed, range 2 | 1125.100 h |
| Operating hours counter reading at overspeed, range 3 | 1125.100 h |
| Operating hours counter reading at overspeed, range 4 | 1026.000 h |
| Operating hours counter reading at overspeed, range 5 | 0.000 h |
| Operating hours counter reading at overspeed, range 6 | 0.000 h |
| Operating hours counter | 1703.400 h |
| -Recall campaigns 3 | 0x00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |
| | 00 00 00 00 00 00 |
| Recall campaigns 4 | 0x00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |
| | 00 00 00 00 00 00 |

| | |
|---------------------------------------|------------------|
| Oxygen storage capacity, bank 1 | 2.23218 |
| Test counter for c.c. diagnosis b1 | 0 |
| Oxygen storage capacity, bank 2 | 2.12305 |
| Test counter for c.c. diagnosis b2 | 0 |
| Engine start temperature | 30.8 °C |
| Calibration ID 1 | 9976186240600000 |
| Calibration ID 2 | |
| CVN | 0x73 33 DA E3 |
| Engine roughness reference value | 10.3473 |
| Misfire detection adaptation, range 2 | 3 |
| Misfire counter cylinder 1 | 0.00 |
| Misfire counter cylinder 6 | 0.00 |
| Misfire counter cylinder 2 | 0.00 |
| Misfire counter cylinder 4 | 0.00 |
| Misfire counter cylinder 3 | 0.00 |
| Misfire counter cylinder 5 | 0.00 |
| Ignition counter misfire detection | 1699.00 |
| Misfire range, minimum rpm | 10200 1 min |
| Misfire range, maximum rpm | 0 1 min |
| Misfire range, minimum load | 99.61 % |
| Misfire range, maximum load | 0.00 % |
| Engine roughness cylinder 1 | 0.479 |
| Engine roughness cylinder 6 | -0.084 |
| Engine roughness cylinder 2 | -0.400 |
| Engine roughness cylinder 4 | 0.555 |
| Engine roughness cylinder 3 | -0.113 |
| Engine roughness cylinder 5 | -0.495 |
| Misfire detection adaptation, range 1 | - |